



WTG-  
QUANTOR  
GMBH

# SR

## TUBE-IN-TUBE COOLING UNIT / HEAT-PUMP

- WEATHER-RESISTANT AND DURABLE
- VERSATILE APPLICATIONS
- IDEAL FOR SMALL TO MEDIUM-SIZED BEVERAGE PRODUCER



IN FLOW WITH YOUR PRODUCTION.

# SR

## TUBE-IN-TUBE COOLING UNIT / HEAT-PUMP

The SR are mobile direct-cooling and heating units, consisting of a cooling aggregate in the upper part and a tubular heat exchanger in the lower part. Heating is performed in the Heat-Pump operation mode. The SR is designed to treat any substance from destalked-grapes to wine, sparkling wine, water, cider, fruit juice and distillates.

The casing of the unit as well as all parts that come in contact with the treated medium are made of stainless steel. The ventilation grills are lacquered in black. Due to its four wheels, this SR unit is easy to manoeuvre. This allows the user to cool or to heat even single tanks or other containers, as required, without the expenditure in an installation. For example: starting a stopped fermentation by heating the tank content. An external cellar-pump for the medium is controlled by the SR's control panel.

The cooling units of the SR series are available in three different sizes / capacities, from 29 to 49,5 kW. They are ideal for small and medium wineries which require the option to heat their wine as well as to cool it and who want to benefit from great flexibility in use. Due to its direct treatment of the medium, the SR offers the most efficient way for cooling or heating.

### APPLICATIONS

- Direct cooling or heating of must for preclearing or at the beginning of fermentation
- Tartaric stabilisation of wines
- Malolactic fermentation (MLF)
- Regulation of fermentation temperature
- Cool storage of wine until bottling
- Unrestricted use in the sparkling wine sector
- Cooling of turbid and solid-containing media, e.g., unfiltered fruit juice
- Room cooling - with appropriate air handlers



### WATER TEMPERATURE RANGE

from -5°C to +45°C (from 23°F to 113°F)

### AMBIENT TEMPERATURE RANGE

from +5°C to +32°C (from 41°F to 89,6°F)

### SUITABLE FOR INDUSTRIES



### CHARACTERISTICS

- ➔ Frigorific circuit with hermetic compressor (Scroll) and high efficiency counter flow evaporator made of stainless steel
- ➔ Heating with Heat-Pump technology
- ➔ Minimum installation effort
- ➔ Stainless steel chassis with wheels
- ➔ All parts that come in contact with the treated medium are made of stainless steel
- ➔ Temperature control by electronic thermostat with digital display
- ➔ Anti-freeze safety device for evaporator
- ➔ Control of an external cellar-pump for the medium by the SR's control panel
- ➔ Refrigerant R407C
- ➔ Protection type of the chiller is minimum IP54.

		SR 9	SR 11	SR 17
TECHNICAL DATA	Cooling capacity *			
	- from 30°C to 25°C	kW 29,0	34,0	49,5
	- from 15°C to 0°C	kW 15,4	18,5	26,3
	Heating capacity	kW 29,0	34,0	50,0
	Electrical supply (other options by inquiry)	400V / 3Ph / 50Hz		
	Max. absorbed power	kW 8,8	9,9	15,6
	Max. current consumption	A 15,6	17,3	26,9
	Number of fans	1	1	2
	Recommended pump flow	hl/h 70-90	80-100	110-140
	Connections	∅ Mâcon 40	Mâcon 40	Mâcon 50
Dimensions:	L	mm 1.050	1.050	1.050
	W	mm 1.050	1.050	1.050
	H	mm 1.750	1.750	2.150
Weight	kg 350	360	360	

\* Cooling capacity at +20°C ambient temperature.  
 Technical specifications are subject to change without notice