WTG-QUANTOR GMBH







DESCRIPTION

The steam generator **TopHeat** is conceived for the production of steam for cleansing and sterilisation of tanks, barrels, pipe systems, cellar equipment and fittings, filters and filling units. The units are made of stainless steel and they are mobile due to their rolls. They are perfectly suited for small wineries, breweries and other beverages producers.

The water in the **TopHeat**'s reservoir (40 liters, or 20 lt by half-fill level) is heated up until steam is created. The heating-up time takes about 15-20 min (40 lt by model TopHeat 18). After the heating at top capacity, use the switch to decrease capacity during the cleaning operation. Operation time for TopHeat 18, for example: approx. 1 hour by full capacity 18kW, and 1,5 hours by 12kW operation capacity, until the container runs empty. The **TopHeat** can then be re-filled and re-heated to continue its operation.

TopHeat is available in three models, with capacities of 12 kW, 18 kW and 24 kW. In all models, after heating at full capacity, decreasing capacity for operation is possible (using the unit's two-position switch). Operation pressure should not exceed 0,5 bar. The **TopHeat** is equipped with a safety pressure valve that opens at 0,8 bar. Steam overflow is evacuated to the floor.

APPLICATIONS

- Cleaning and sterilisation of tanks and barrels
- Cleaning of pipe systems, cellar equipment and fittings
- Cleaning of filters and filling units

	Model	TopHeat		TopHeat 18		TopHeat 24	
TECHNICAL DATA	Heating capacity	12 kW		18 kW		24 kW	
	Operation capacity	9 kW		12 kW		18 kW	
	Steam quantity	max. 18 kg/h		max. 27 kg/h		max. 36 kg/h	
	Operation time (approx.)			Full: Half full:			
	Electric connection	400V/3Ph/50Hz T + N 32A		400V/3Ph/50Hz T + N 32A		400V/3Ph/50Hz T + N 63A	
	Electric fuse	3 x 25A		3 x 25A		3 x 36A	
	Steam Connections Water connections	1" ¾" (female)					
	Dimensions (L x W x H) Weight	490 x 400 x 730 (1.030) mm 45 kg					

Specifications subject to change.